

P/N 204-13555-1

Description

Fastener Length: 3-5/16", Thread: 1/2-20, Thread Length: 51/64

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: 204135551

Minimum Qty (MOQ):

NSN: 5305-01-019-0758

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N 204-13555-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.802 Inches Nominal
Fastener Length:	3.340 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.717 Inches Nominal
Grip Diameter:	0.4985 Inches Minimum And 0.4995 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.500 Inches
Grip Length:	2.438 Inches Nominal
Thread Quantity Per Inch:	20
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Grip
Material:	Steel Overall
Material Document And Classification:	Ph13-8mo Bms7-189 Fscm 81205 Mfr Ref Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/204-13555-1 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/204-13555-1 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/204-13555-1 and selecting the quantity you want then click "add to cart".