

Description

Fastener Length: 5/16", Thread: 2-56, Thread Length: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M110002A
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-207-7544
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3M1100-02A Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.160 Inches Nominal
Fastener Length:	0.340 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.147 Inches Minimum And 0.153 Inches Maximum
Head Height:	0.037 Inches Minimum And 0.043 Inches Maximum
Shoulder Diameter:	0.103 Inches Minimum And 0.107 Inches Maximum First Shoulder
Shoulder Length:	0.165 Inches Minimum And 0.175 Inches Maximum First Shoulder
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Shoulder Shape:	Round First Shoulder
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M1100-02A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.