

Description

Fastener Length: 1-19/32", Thread: 1/4-24, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN2525A
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-151-1991
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN25-25A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.359 Inches Maximum
Fastener Length:	1.609 Inches Nominal
Head Style:	Button
Head Diameter:	0.625 Inches Nominal
Head Height:	0.156 Inches Nominal
Groove Diameter:	0.245 Inches Minimum And 0.255 Inches Maximum
Single Shear Strength:	5750 Pounds Per Square Inch
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	3250 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall Or Dichromate Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN25-25A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.