

Description

Thread Size: 1/4", Length: 1-3/4", Thread Length: 7/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN490HT6
Minimum Qty (MOQ):	2
NSN:	5340-00-141-6459
Schedule B:	7228.40.0000
ECCN:	EAR99
National Motor Freight:	063520, Waveguide In Boxes / Crates

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN490HT6 Specifications

Thread Class:	3a Overall
Thread Direction:	Right-hand Overall
Thread Length:	0.927 Inches Minimum Rod Connection And 0.947 Inches Maximum Rod Connection
Overall Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Flange Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Unthreaded End Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Metallic Hardness Rating:	25.0 Minimum Rockwell C And 30.0 Maximum Rockwell C
Flange Width:	0.115 Inches Minimum And 0.135 Inches Maximum
Unthreaded End Outside Diameter:	0.303 Inches Minimum And 0.305 Inches Maximum
Unthreaded End Inside Diameter:	0.169 Inches Minimum And 0.201 Inches Maximum
Unthreaded End Depth:	0.549 Inches Minimum And 0.579 Inches Maximum
Nominal Thread Size:	0.250 Inches Rod Connection
Material:	Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response Overall
Style Designator:	External Thread, Flanged, Tubular End
Thread Series Designator:	Unf Rod Connection

How to Order

Order this threaded rod end from our inventory online by visiting <https://military-fasteners.com/rod+ends/threaded+rod+ends/AN490HT6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.