

P/N CR2248-4-4

Description

Fastener Length: 3/8", CR2248 series rivet

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

Alternate Part Numbers

CR2248-4-04

SKU / Model: CR224844

Minimum Qty (MOQ): 100

NSN: 5320-00-958-6194

ECCN: EAR99

National Motor Freight: 013630, Alum Rivets



^{*} See page 2 for technical characteristics

P/N CR2248-4-4 Specifications

Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	619 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
Material:	Steel Comp E4340 Stem Or Steel Comp 4340 Stem Or Steel Comp 8740 Stem
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Stem Or Mil-s-5000 Mil Spec 2nd Material Response Stem Or Mil-s-6049 Mil Spec 3rd Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Locking Ring
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1739 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR2248-4-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR2248-4-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR2248-4-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR2248-4-4 and selecting the quantity you want then