

P/N HL218-10-16

Description

Fastener Length: 1-1/2", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: HL2181016

Minimum Qty (MOQ): 10 EA

NSN: 5320-01-303-5687

Schedule B: 7318.24.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE AVAILABLE

^{*} See page 2 for technical characteristics

P/N HL218-10-16 Specifications

3a
Right-hand
Bronze
1.490 Inches Minimum And 1.510 Inches Maximum
Err-090
0.068 Inches Minimum And 0.078 Inches Maximum
0.1270 Inches Minimum And 0.1295 Inches Maximum
0.3422 Inches Minimum And 0.3432 Inches Maximum
Pin-rivet, Straight, Threaded
0.475 Inches Minimum And 0.505 Inches Maximum
Cetyl Alcohol, Spec 305, Hi-shear Corp
1.005 Inches Maximum
24
160000 Pounds Per Square Inch
0.312 Inches
95000 Single Pounds Per Square Inch
Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Unjf

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin rivets/HL218-10-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/pin rivets/HL218-10-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/pin rivets/HL218-10-16 and selecting the quantity you want then click "add to cart".