

P/N HL218-6-7

Description

protruding shear head, oversized for hl18, alloy steel cadmium plated

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: HL21867

Minimum Qty (MOQ): 20

NSN: 5320-00-494-7985

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N HL218-6-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Quantity Per Inch:	32
Hardness Rating:	28.0 Rockwell C Minimum And 35.0 Rockwell C Maximum Overall
Material:	Steel Comp 4130 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response Or Mil-s-6098 Mil Spec 3rd Material Response Or Mil-s-6049 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	81205-bacb30kk Manufacturers Standard

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin rivets/HL218-6-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/pin rivets/HL218-6-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/pin rivets/HL218-6-7 and selecting the quantity you want then click "add to cart".