

Description

Fastener Length: 1-5/64", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL40811
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-333-8881
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL40-8-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.073 Inches Minimum And 1.083 Inches Maximum
Head Style:	Err-090
Head Height:	0.059 Inches Minimum And 0.069 Inches Maximum
Width Between Flats:	0.0947 Inches Minimum And 0.0967 Inches Maximum
Shank Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.387 Inches Minimum And 0.412 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.683 Inches Minimum And 0.693 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Spec,258,cagec 92215 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL40-8-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.