

Description

MS16562-19 Spring Pin

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1656219
Minimum Qty (MOQ):	100
NSN:	5315-00-271-7464
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N MS16562-19 Specifications

<b>Overall Length:</b>	0.860 Inches Minimum And 0.890 Inches Maximum
<b>Diameter:</b>	0.083 Inches Minimum And 0.086 Inches Maximum
<b>Material Thickness:</b>	0.018 Inches Nominal
<b>Hardness Rating:</b>	46.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
<b>Shear Strength:</b>	650 Double Pound
<b>Material:</b>	Steel Comp 1070 Overall Or Steel Comp 1074 Overall Or Steel Comp 1080 Overall Or Steel Comp 1086 Overall Or Steel Comp 1095 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty2 Cl2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Slotted

## How to Order

Order this spring pin from our inventory online by visiting <https://military-fasteners.com/pins/spring+pins/MS16562-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.