

P/N MS20426A3-5-5

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS20426A355

Minimum Qty (MOQ): 1000 EA

NSN: 5320-01-577-8793



^{*} See page 2 for technical characteristics

P/N MS20426A3-5-5 Specifications

| Fastener Length: | 0.625 Inches Nominal |
|-------------------------------------------|--------------------------------------------------------------------------------|
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.094 Inches Nominal |
| Shank Style: | Straight |
| Head Major Diameter: | 0.175 Inches Minimum And 0.183 Inches Maximum |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Part Name Assigned By Controlling Agency: | Rivet, Solid, Countersunk 100 Degree, Precision Head |
| Material: | Aluminum Alloy 1100 Overall |
| Material Document And Classification: | Sae-ams Qq-a-430 Assn Std Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20426A3-5-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/MS20426A3-5-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/MS20426A3-5-5 and selecting the quantity you want then click "add to cart".