

Description

Thread: 3/8-24, self locking, reduced hexagon, reduced height, corrosion and heat resistant steel, silver plated, MS21043 series

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS210436
Minimum Qty (MOQ):	10
NSN:	5310-00-881-0943
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21043-6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.620 Inches Maximum
Counterbore Diameter:	0.375 Inches Minimum Nut And 0.405 Inches Maximum Nut
Lubrication:	Soluble Lubricant
Overall Height:	0.267 Inches Minimum And 0.282 Inches Maximum
Nut Style:	Hexagon
Washer Thickness:	0.030 Inches Minimum
Nut Counterbore Depth:	0.008 Inches Minimum Nut And 0.042 Inches Maximum Nut
Width Across Flats:	0.430 Inches Minimum And 0.440 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall
Precious Material And Location:	External Surface Silver
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Qq-s-365 Fed Spec Single Treatment Response Overall Or Ams 2410 Assn Std Single Treatment Response Overall

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/MS21043-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.