

Description

Fastener Length: 1-3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097AD628
Minimum Qty (MOQ):	130 EA
NSN:	5320-01-234-5247
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N NAS1097AD6-28 Specifications

<b>Fastener Length:</b>	1.740 Inches Minimum And 1.760 Inches Maximum
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.004 Inches Minimum And 0.006 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.189 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.3016 Inches Maximum
<b>Head Minor Diameter:</b>	0.198 Nominal Mils And 0.208 Nominal Centimeters
<b>Countersink Height:</b>	0.046 Inches Nominal
<b>Shear Strength:</b>	26000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430,t4 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097AD6-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.