

P/N NAS1101E3-27

Description

Fastener Length: 1-11/16", Thread: 10-32, Thread Length: 1-11/16"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS1101E327

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-388-9096

National Motor Freight: 096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N NAS1101E3-27 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.626 Inches Minimum And 1.688 Inches Maximum
Fastener Length:	1.626 Inches Minimum And 1.688 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.306 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.103 Inches Minimum And 0.118 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1101 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1101E3-27 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1101E3-27 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1101E3-27 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1101E3-27 and selecting the quantity you want of the property of the