

## P/N 002-004466-004

### **Description**

Diameter: 17/64", 303 steel

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	002004466004
Minimum Qty (MOQ):	1
NSN:	5325-01-096-1341
Schedule B:	8803.30.0030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



<sup>\*</sup> See page 2 for technical characteristics

# P/N 002-004466-004 Specifications

Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Diameter:	0.270 Inches Maximum
Securing Device Type:	Ring
Turnlock Stud Shank Style:	Stud Shank
Extension Length:	0.155 Inches Nominal
Turnlock Stud Head Style:	Fillister
Drive Type:	Slotted
Stud Thread Size And Series/type Designator:	0.112-40 Unc
Stud Shank Major Diameter:	0.184 Inches Minimum And 0.186 Inches Maximum
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A582 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

## **How to Order**

Order this turnlock fastener stud from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+studs/002-004466-004">https://military-fasteners.com/studs/turnlock+fastener+studs/002-004466-004</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/studs/turnlock+fastener+studs/002-004466-004">https://military-fasteners.com/studs/turnlock+fastener+studs/002-004466-004</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/studs/turnlock+fastener+studs/002-004466-004">https://military-fasteners.com/studs/turnlock+fastener+studs/002-004466-004</a> and selecting the quantity you want then click "add to cart".