

**Description**

Fastener Length: 13/16", Thread: 6-32, Thread Length: 1/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	003008487003
Minimum Qty (MOQ):	1
NSN:	5305-01-005-8631
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N 003-008487-003 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.115 Inches Minimum And 0.135 Inches Maximum
<b>Fastener Length:</b>	0.812 Inches Minimum And 0.822 Inches Maximum
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.256 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.087 Inches Minimum And 0.097 Inches Maximum
<b>First Diameter From Head:</b>	0.096 Inches Minimum And 0.099 Inches Maximum
<b>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</b>	0.687 Inches Minimum And 0.697 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	An/alq-135(v)
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	130000 Pounds Per Square Inch
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Externally Relieved Body Diameter Quantity:</b>	1
<b>Material:</b>	Steel Comp 410 Overall
<b>Material Document And Classification:</b>	Qq-s-763,cond H Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/003-008487-003> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.