



Military-Fasteners.com

P/N 003-008487-003

Description

Fastener Length: 13/16", Thread: 6-32, Thread Length: 1/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	003008487003
Minimum Qty (MOQ):	1
NSN:	5305-01-005-8631
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 003-008487-003 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Fastener Length:	0.812 Inches Minimum And 0.822 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
First Diameter From Head:	0.096 Inches Minimum And 0.099 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.687 Inches Minimum And 0.697 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	An/alq-135(v)
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Externally Relieved Body Diameter Quantity:	1
Material:	Steel Comp 410 Overall
Material Document And Classification:	Qq-s-763,cond H Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/003-008487-003> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.