

Description

Fastener Length: 5/8", Thread: 5/16-24, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	116026501
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-830-1643
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 1-160-265-01 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.421 Inches Minimum And 0.436 Inches Maximum
Fastener Length:	0.620 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.600 Inches Minimum And 0.635 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Hardness Rating:	23.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 1022
Screw Material Document And Classification:	Ams 5070 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/1-160-265-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.