

P/N 1009376

Description

Overall Length: 2-1/4", Thread: 1/8-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: 1009376

Minimum Qty (MOQ): 1 EA

NSN: 5305-00-579-4992

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N 1009376 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Minimum
Fastener Length:	2.280 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.312 Inches Nominal
Head Height:	0.123 Inches Minimum And 0.130 Inches Maximum
Shoulder Diameter:	0.1170 Inches Minimum Second Shoulder And 0.1270 Inches Maximum Second Shoulder
Shoulder Diameter:	0.1996 Inches Minimum First Shoulder And 0.1999 Inches Maximum First Shoulder
Shoulder Length:	0.180 Inches Nominal Second Shoulder
Shoulder Length:	1.620 Inches Nominal First Shoulder
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Shoulder Shape:	Round All Shoulders
Material:	Steel Comp 304 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/1009376 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/1009376 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/1009376 and selecting the quantity you want then