

Description

Thread Size: 13/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	102741143
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-283-6478
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 10274114-3 Specifications

Thread Class:	3b
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.309 Inches Minimum And 0.312 Inches Maximum
Shank Style:	Blind Rivet, Nut And Bolt (assembly)
Head Major Diameter:	0.372 Inches Maximum
Expansion Device:	Expander
Lubrication:	Dry Film
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Features Provided:	Self-locking
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Shear Strength:	125000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Furnished W/o Bolt
Material:	Steel Comp 431 Expander
Material:	Steel Comp 304 Sleeve Or Steel Comp 305 Sleeve
Material Document And Classification:	Ams 5628 Assn Std Single Material Response Expander
Material Document And Classification:	Qq-s-763 Fed Spec All Material Responses Sleeve
Surface Treatment:	Passivate Sleeve
Surface Treatment Document And Classification:	Qq-p-35,ty 1 Fed Spec Single Treatment Response Sleeve
Thread Series Designator:	Unjf

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/10274114-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.