

**Description**

Thread Size: 13/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	102741143
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-283-6478
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N 10274114-3 Specifications

<b>Thread Class:</b>	3b
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.309 Inches Minimum And 0.312 Inches Maximum
<b>Shank Style:</b>	Blind Rivet, Nut And Bolt (assembly)
<b>Head Major Diameter:</b>	0.372 Inches Maximum
<b>Expansion Device:</b>	Expander
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Features Provided:</b>	Self-locking
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Shear Strength:</b>	125000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Special Features:</b>	Furnished W/o Bolt
<b>Material:</b>	Steel Comp 431 Expander
<b>Material:</b>	Steel Comp 304 Sleeve Or Steel Comp 305 Sleeve
<b>Material Document And Classification:</b>	Ams 5628 Assn Std Single Material Response Expander
<b>Material Document And Classification:</b>	Qq-s-763 Fed Spec All Material Responses Sleeve
<b>Surface Treatment:</b>	Passivate Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-35,ty 1 Fed Spec Single Treatment Response Sleeve
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/10274114-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.