

**Description**

Fastener Length: 13/16", Thread: 10-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	10851009
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-881-6071
Schedule B:	7318.15.6080
ECCN:	N/A
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N 10851-009 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.312 Inches Minimum
<b>Fastener Length:</b>	0.843 Inches Nominal
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.375 Inches Nominal
<b>Head Height:</b>	0.187 Inches Nominal
<b>First Diameter From Head:</b>	0.131 Inches Minimum And 0.136 Inches Maximum
<b>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</b>	0.531 Inches Nominal
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Externally Relieved Body Diameter Quantity:</b>	1
<b>Material:</b>	Steel Comp 303 Overall
<b>Material Document And Classification:</b>	Aisi Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this captive screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/10851-009> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.