

Description

Fastener Length: 11/16", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	110121T35
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-107-9192
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N 110121T3-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.337 Inches Minimum And 0.389 Inches Maximum
Fastener Length:	0.659 Inches Minimum And 0.691 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.258 Inches Minimum And 0.305 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Grip
Material:	Titanium Alloy Overall
Material Document And Classification:	Nas 621,6al-4v Assn Std 1st Material Response Overall Or Ams 4928 Assn Std 2nd Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/110121T3-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.