

Description

cadmium plated steel slotted recess - total panel thickness 0.300" - 0.329"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	112600010
Minimum Qty (MOQ):	10
NSN:	5325-00-290-3970
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

# P/N 1126000-10 Specifications

Diameter:	0.305 Inches Nominal
Securing Device Type:	Washer
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.812 Inches Minimum And 0.827 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.270 Inches Minimum And 0.329 Inches Maximum
Drive Type:	Slotted
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126000-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.