

Description

cadmium plated steel slotted recess - total panel thickness 0.420" - 0.449"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | 112600014 |
| Minimum Qty (MOQ): | 4 |
| NSN: | 5325-00-298-7002 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |

NO IMAGE
AVAILABLE

P/N 1126000-14 Specifications

| | |
|--|---|
| Diameter: | 0.500 Inches Nominal |
| Securing Device Type: | Washer |
| Turnlock Stud Head Style: | Fillister |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.932 Inches Minimum And 0.947 Inches Maximum |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.390 Inches Minimum |
| Drive Type: | Slotted |
| Stud Head Height: | 0.093 Inches Nominal |
| Material: | Steel Comp 1009 Eyelet |
| Material: | Steel Comp 4037 Stud |
| Material: | Steel Ejector Spring |
| Material: | Steel Pin |
| Material Document And Classification: | Astm A109 Assn Std Single Material Response Eyelet |
| Material Document And Classification: | Astm A547 Assn Std Single Material Response Stud |
| Material Document And Classification: | Qq-w-470 Fed Spec Single Material Response Ejector Spring |
| Material Document And Classification: | Qq-w-470 Fed Spec Single Material Response Pin |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,cl 2,ty 2 Fed Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126000-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.