

**Description**

cadmium plated steel slotted recess - total panel thickness 0.060" - 0.089"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	11260002
Minimum Qty (MOQ):	10
NSN:	5325-00-449-3022
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE  
AVAILABLE

## P/N 1126000-2 Specifications

<b>Diameter:</b>	0.298 Inches Minimum And 0.308 Inches Maximum
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.572 Inches Minimum And 0.587 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.030 Inches Minimum And 0.089 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Stud Head Height:</b>	0.298 Inches Minimum And 0.308 Inches Maximum
<b>Material:</b>	Steel Comp 4037 Stud
<b>Material:</b>	Steel Eyelet
<b>Material:</b>	Steel Pin
<b>Material Document And Classification:</b>	Astm A322 Assn Std 1st Material Response Stud Or Astm A331 Assn Std 2nd Material Response Stud
<b>Material Document And Classification:</b>	Qq-w-470 Fed Spec Single Material Response Pin
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126000-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.