

Description

cadmium plated steel slotted recess - total panel thickness 0.060" - 0.089"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 11260002 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-00-449-3022 |
| National Motor Freight: | 093490, Bolt / Nut / Screw / Clips / Fastener / Etc |

NO IMAGE
AVAILABLE

P/N 1126000-2 Specifications

| | |
|--|--|
| Diameter: | 0.298 Inches Minimum And 0.308 Inches Maximum |
| Turnlock Stud Head Style: | Fillister |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.572 Inches Minimum And 0.587 Inches Maximum |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.030 Inches Minimum And 0.089 Inches Maximum |
| Drive Type: | Slotted |
| Stud Head Height: | 0.298 Inches Minimum And 0.308 Inches Maximum |
| Material: | Steel Comp 4037 Stud |
| Material: | Steel Eyelet |
| Material: | Steel Pin |
| Material Document And Classification: | Astm A322 Assn Std 1st Material Response Stud Or Astm A331 Assn Std 2nd Material Response Stud |
| Material Document And Classification: | Qq-w-470 Fed Spec Single Material Response Pin |
| Surface Treatment: | Cadmium Overall And Chromate Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126000-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.