

Description

cadmium plated steel slotted recess - total panel thickness 0.120" - 0.149"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 11260004 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-01-179-7415 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 1126000-4 Specifications

| | |
|--|---|
| Diameter: | 0.298 Inches Minimum And 0.308 Inches Maximum |
| Securing Device Type: | Ring |
| Turnlock Stud Head Style: | Flat Fillister |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.609 Inches Nominal |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.120 Inches Minimum And 0.149 Inches Maximum |
| Drive Type: | Slotted |
| Stud Head Height: | 0.088 Inches Minimum And 0.098 Inches Maximum |
| Material: | Steel Ejector Springsteel Comp 1009 Eyeletsteel Pinsteel Comp 4037 Stud |
| Material Document And Classification: | Astm A547 Assn Std Single Material Response Ejector Springastm A109 Assn Std Single Material Response Eyeletastm A228 Assn Std Single Material Response Pinastm A547 Assn Std Single Material Response Stud |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126000-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.