

Description

cadmium plated steel slotted recess - total panel thickness 0.120" - 0.149"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	11260004
Minimum Qty (MOQ):	10
NSN:	5325-01-179-7415
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 1126000-4 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Securing Device Type:	Ring
Turnlock Stud Head Style:	Flat Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.609 Inches Nominal
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.120 Inches Minimum And 0.149 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.088 Inches Minimum And 0.098 Inches Maximum
Material:	Steel Ejector Springsteel Comp 1009 Eyeletsteel Pinsteel Comp 4037 Stud
Material Document And Classification:	Astm A547 Assn Std Single Material Response Ejector Springastm A109 Assn Std Single Material Response Eyeletastm A228 Assn Std Single Material Response Pinastm A547 Assn Std Single Material Response Stud
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting<https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126000-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out[here](#) to complete your order.