

Description

total panel thickness: 0.240" - 0.269", cadmium plated steel, slotted recess, 1126000 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[2600-8](#)

SKU / Model:	11260008
Minimum Qty (MOQ):	5
NSN:	5325-01-211-6924
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N 1126000-8 Specifications

Diameter:	0.500 Inches Nominal
Securing Device Type:	Spring
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.527 Inches Nominal
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.240 Inches Minimum And 0.269 Inches Maximum
Drive Type:	Slotted
Features Provided:	All Metal Locking Element
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	02731-hs4431 Manufacturers Standard

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126000-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.