

Description

total panel thickness: 0.240" - 0.269", cadmium plated steel, slotted recess, 1126000 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[2600-8](#)

| | |
|-------------------------|-----------------------------|
| SKU / Model: | 11260008 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-01-211-6924 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N 1126000-8 Specifications

| | |
|--|--|
| Diameter: | 0.500 Inches Nominal |
| Securing Device Type: | Spring |
| Turnlock Stud Head Style: | Fillister |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.527 Inches Nominal |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.240 Inches Minimum And 0.269 Inches Maximum |
| Drive Type: | Slotted |
| Features Provided: | All Metal Locking Element |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 02731-hs4431 Manufacturers Standard |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126000-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.