

**Description**

total panel thickness: 0.240" - 0.269", cadmium plated steel, slotted recess, 1126000 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

2600-8

SKU / Model:	11260008
Minimum Qty (MOQ):	5
NSN:	5325-01-211-6924
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N 1126000-8 Specifications

<b>Diameter:</b>	0.500 Inches Nominal
<b>Securing Device Type:</b>	Spring
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.527 Inches Nominal
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.240 Inches Minimum And 0.269 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Features Provided:</b>	All Metal Locking Element
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	02731-hs4431 Manufacturers Standard

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126000-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.