

Description

Quarter turn (1/4 turn), cadmium plated steel, philips recess, total panel thickness 0.360" - 0.389", 1126004 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

26S8-12

SKU / Model:	112600412
Minimum Qty (MOQ):	10
NSN:	5325-00-117-4813
Schedule B:	7318.15.5060
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 1126004-12 Specifications

Diameter:	0.500 Inches Nominal
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.872 Inches Minimum And 0.887 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.330 Inches Minimum And 0.389 Inches Maximum
Drive Type:	Cross Recess
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126004-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.