

Description

cadmium plated steel philips recess, total panel thickness 0.510" - 0.539

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[26S8-17](#)

| | |
|-------------------------|--|
| SKU / Model: | 112600417 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5325-00-514-9369 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



* See page 2 for technical characteristics

P/N 1126004-17 Specifications

| | |
|--|---|
| Diameter: | 0.303 Inches Nominal |
| Securing Device Type: | Washer |
| Turnlock Stud Head Style: | Fillister |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.441 Inches Nominal |
| Eyelet Outside Diameter: | 0.247 Inches Nominal |
| Eyelet Length: | 0.332 Inches Nominal |
| Material Accommodated Thickness: | 0.510 Inches Minimum And 0.539 Inches Maximum |
| Drive Type: | Cross Recess |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126004-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.