

**Description**

Quarterturn 1/4, cadmium plated overall, 1126004 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	112600420
Minimum Qty (MOQ):	5
NSN:	5325-00-775-6461
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

# P/N 1126004-20 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Securing Device Type:	Spring
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	1.112 Inches Minimum And 1.127 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.600 Inches Minimum And 0.629 Inches Maximum
Drive Type:	Cross Recess
Material:	Steel Overall
Surface Treatment:	Cadmium Overall

## How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126004-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.