

Description

cadmium plated steel philips recess - total panel thickness 0.210" - 0.239

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[26S8-7](#)

SKU / Model:	11260047
Minimum Qty (MOQ):	10
NSN:	5325-00-995-8345
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE
AVAILABLE

P/N 1126004-7 Specifications

Diameter:	0.480 Inches Minimum And 0.520 Inches Maximum
Securing Device Type:	Spring
Turnlock Stud Head Style:	Fillister Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.722 Inches Minimum And 0.737 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.180 Inches Minimum And 0.239 Inches Maximum
Drive Type:	Cross Recess
Stud Head Height:	0.440 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126004-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.