

Description

cadmium plated steel philips recess - total panel thickness 0.240" - 0.269"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | 11260048 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-00-687-5689 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |

NO IMAGE
AVAILABLE

P/N 1126004-8 Specifications

| | |
|--|---|
| Diameter: | 0.298 Inches Minimum And 0.308 Inches Maximum |
| End Item Identification: | 1520-01-035-0266 Helicopter, Utility |
| Turnlock Stud Head Style: | Flat Fillister |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.752 Inches Minimum And 0.767 Inches Maximum |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.322 Inches Nominal |
| Material Accommodated Thickness: | 0.240 Inches Minimum And 0.269 Inches Maximum |
| Drive Type: | Cross Recess |
| Stud Head Height: | 0.088 Inches Minimum And 0.098 Inches Maximum |
| Part Name Assigned By Controlling Agency: | Stud Assembly, Turnlock |
| Material: | Steel Comp 4037 Stud |
| Material: | Steel Ejector Spring |
| Material: | Steel Eyelet |
| Material Document And Classification: | Qq-s-640 Fed Spec Single Material Response Eyelet |
| Material Document And Classification: | Qq-w-470 Fed Spec Single Material Response Ejector Spring |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126004-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.