

## Description

corrosion resistant steel, slotted recess, total panel thickness 0.090" - 0.119

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[2600-3S](#)

SKU / Model:	11260073
Minimum Qty (MOQ):	5
NSN:	5325-00-687-3842
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



## P/N 1126007-3 Specifications

<b>Diameter:</b>	0.298 Inches Minimum And 0.308 Inches Maximum
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.602 Inches Minimum And 0.617 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.060 Inches Minimum And 0.119 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Passivate Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126007-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.