

Description

corrosion resistant steel, slotted recess, total panel thickness 0.090" - 0.119

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[2600-3S](#)

SKU / Model:	11260073
Minimum Qty (MOQ):	5
NSN:	5325-00-687-3842
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 1126007-3 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.602 Inches Minimum And 0.617 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.060 Inches Minimum And 0.119 Inches Maximum
Drive Type:	Slotted
Material:	Steel Overall
Surface Treatment:	Passivate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126007-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.