

Description

corrosion resistant steel - slotted recess - total panel thickness 0.150" - 0.179"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	11260075
Minimum Qty (MOQ):	10
NSN:	5325-00-646-8088
National Motor Freight:	094533, Eyelets Or Eyelet Hooks Noi

NO IMAGE
AVAILABLE

P/N 1126007-5 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Turnlock Stud Head Style:	Flat Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.662 Inches Minimum And 0.677 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.150 Inches Minimum And 0.179 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.088 Inches Minimum And 0.098 Inches Maximum
Material:	Steel Overall
Surface Treatment:	Passivate Overall
Specification/standard Data:	71286-2600-5s Manufacturers Standard

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126007-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.