

Description

panel thickness 0.18" - 0.209", corrosion resistant steel, slotted recess, 1126007 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	11260076
Minimum Qty (MOQ):	10
NSN:	5325-00-543-3410
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 1126007-6 Specifications

Diameter:	0.308 Inches Nominal
Securing Device Type:	Spring
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.692 Inches Minimum And 0.707 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.180 Inches Minimum And 0.209 Inches Maximum
Drive Type:	Slotted
Material:	Steel Overall
Surface Treatment:	Passivate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126007-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.