

## P/N 1126007-6

### **Description**

panel thickness 0.18" - 0.209", corrosion resistant steel, slotted recess, 1126007 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: 11260076

Minimum Qty (MOQ): 10

NSN: 5325-00-543-3410

National Motor Freight: 066440, Fasteners Curtain / Snap Metal









# P/N 1126007-6 Specifications

Diameter:	0.308 Inches Nominal
Securing Device Type:	Spring
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.692 Inches Minimum And 0.707 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.180 Inches Minimum And 0.209 Inches Maximum
Drive Type:	Slotted
Material:	Steel Overall
Surface Treatment:	Passivate Overall

## **How to Order**

Order this turnlock fastener stud assembly from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126007-6">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126007-6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126007-6">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126007-6</a>