

**Description**

corrosion resistant steel - slotted recess - total panel thickness 0.240" - 0.269"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	11260078
Minimum Qty (MOQ):	10
NSN:	5325-00-550-0711
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE  
AVAILABLE

## P/N 1126007-8 Specifications

<b>Diameter:</b>	0.302 Inches Nominal
<b>Securing Device Type:</b>	Washer
<b>Turnlock Stud Head Style:</b>	Flat Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.752 Inches Minimum And 0.767 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.210 Inches Minimum And 0.269 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Stud Head Height:</b>	0.093 Inches Nominal
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Passivate Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126007-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.