

Description

corrosion resistant steel - slotted recess - total panel thickness 0.270" - 0.299"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	11260079
Minimum Qty (MOQ):	10
NSN:	5325-00-649-8557
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 1126007-9 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Turnlock Stud Head Style:	Flat Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.781 Inches Minimum And 0.797 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.270 Inches Minimum And 0.299 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.088 Inches Minimum And 0.098 Inches Maximum
Material:	Steel Overall
Surface Treatment:	Passivate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126007-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.