

**Description**

corrosion resistant steel - philips recess - total panel thickness 0.180" - 0.209"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	11260086
Minimum Qty (MOQ):	10
NSN:	5325-00-781-1456
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE  
AVAILABLE

## P/N 1126008-6 Specifications

<b>Diameter:</b>	0.298 Inches Minimum And 0.308 Inches Maximum
<b>Securing Device Type:</b>	Spring
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.669 Inches Nominal
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.180 Inches Minimum And 0.209 Inches Maximum
<b>Drive Type:</b>	Cross Recess
<b>Material:</b>	Steel Comp 302 Ejector Spring
<b>Material:</b>	Steel Comp 302 Stud Or Steel Corrosion Resisting Stud
<b>Material:</b>	Steel Comp 302 Pin
<b>Material:</b>	Steel Comp 305 Eyelet
<b>Material Document And Classification:</b>	Qq-w-423 Fed Spec 1st Material Response Stud Or Carp Enter No. 10 Cagec 71321 Mfr Ref 2nd Material Response Stud
<b>Material Document And Classification:</b>	Qq-w-423 Fed Spec Single Material Response Ejector Spring
<b>Material Document And Classification:</b>	Qq-w-423 Fed Spec Single Material Response Pin
<b>Material Document And Classification:</b>	Qq-s-766 Fed Spec Single Material Response Eyelet
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126008-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.