

P/N 1126008-6

Description

corrosion resistant steel - philips recess - total panel thickness 0.180" - 0.209"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: 11260086

Minimum Qty (MOQ): 10

NSN: 5325-00-781-1456

National Motor Freight: 066440, Fasteners Curtain / Snap Metal



^{*} See page 2 for technical characteristics

P/N 1126008-6 Specifications

Diameter:	0.298 Inches Minimum And 0.308 Inches Maximum
Securing Device Type:	Spring
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.669 Inches Nominal
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.180 Inches Minimum And 0.209 Inches Maximum
Drive Type:	Cross Recess
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud Or Steel Corrosion Resisting Stud
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Material Document And Classification:	Qq-w-423 Fed Spec 1st Material Response Stud Or Carp Enter No. 10 Cagec 71321 Mfr Ref 2nd Material Response Stud
Material Document And Classification:	Qq-w-423 Fed Spec Single Material Response Ejector Spring
Material Document And Classification:	Qq-w-423 Fed Spec Single Material Response Pin
Material Document And Classification:	Qq-s-766 Fed Spec Single Material Response Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126008-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.