

**Description**

corrosion resistant steel, total panel thickness 0.150" - 0.179

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[2600-5SW](#)

SKU / Model:	11260145
Minimum Qty (MOQ):	5
NSN:	5325-00-810-8509
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 1126014-5 Specifications

<b>Head Length:</b>	0.700 Inches Minimum And 0.740 Inches Maximum
<b>Turnlock Stud Head Style:</b>	Flat Fillister Wing
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.662 Inches Minimum And 0.677 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.322 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.120 Inches Minimum And 0.539 Inches Maximum
<b>Stud Head Height:</b>	0.480 Inches Minimum And 0.520 Inches Maximum
<b>Material:</b>	Steel Comp 302 Ejector Spring
<b>Material:</b>	Steel Comp 302 Stud
<b>Material:</b>	Steel Comp 304 Eyelet
<b>Material:</b>	Steel Comp 302 Pin
<b>Surface Treatment:</b>	Passivate Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126014-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.