

P/N 1126014-5

Description

corrosion resistant steel, total panel thickness 0.150" - 0.179

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

Alternate Part Numbers

2600-5SW

SKU / Model: 11260145

Minimum Qty (MOQ):

NSN: 5325-00-810-8509

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal







^{*} See page 2 for technical characteristics

P/N 1126014-5 Specifications

Head Length:	0.700 Inches Minimum And 0.740 Inches Maximum
Turnlock Stud Head Style:	Flat Fillister Wing
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.662 Inches Minimum And 0.677 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.322 Inches Nominal
Material Accommodated Thickness:	0.120 Inches Minimum And 0.539 Inches Maximum
Stud Head Height:	0.480 Inches Minimum And 0.520 Inches Maximum
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud
Material:	Steel Comp 304 Eyelet
Material:	Steel Comp 302 Pin
Surface Treatment:	Passivate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126014-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1126014-5