

Description

total panel thickness: 0.060 - 0.089", cadmium plated steel, slotted recess, quarterturn, 1127000 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | 11270002 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-00-236-3914 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



P/N 1127000-2 Specifications

| | |
|--|---|
| Diameter: | 0.244 Inches Minimum And 0.256 Inches Maximum |
| Turnlock Stud Head Style: | Stud Head |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 1.061 Inches Minimum And 1.071 Inches Maximum |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.328 Inches Nominal |
| Material Accommodated Thickness: | 0.600 Inches Minimum And 0.659 Inches Maximum |
| Drive Type: | Slotted |
| Stud Head Height: | 0.069 Inches Minimum And 0.076 Inches Maximum |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |

How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/1127000-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.