

Description

total panel thickness 0.120" - 0.149", cadmium plated steel, slotted recess, quarterturn, 1127000 series stud

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	11270004
Minimum Qty (MOQ):	10
NSN:	5325-00-298-7001
Schedule B:	7318.15.5030
ECCN:	EAR99



P/N 1127000-4 Specifications

Diameter:	0.251 Inches Minimum And 0.256 Inches Maximum
Securing Device Type:	Washer
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.560 Inches Minimum And 0.570 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.328 Inches Nominal
Material Accommodated Thickness:	0.120 Inches Minimum And 0.149 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.072 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1127000-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.