

# P/N 1127000-7

### **Description**

cadmium plated steel, slotted recess, total panel thickness: 0.210 - 0.239

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: 11270007

Minimum Qty (MOQ): 10

NSN: 5325-01-242-6074

National Motor Freight: 066440, Fasteners Curtain / Snap Metal



<sup>\*</sup> See page 2 for technical characteristics

# P/N 1127000-7 Specifications

Diameter:	0.251 Inches Minimum And 0.256 Inches Maximum
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.641 Inches Minimum And 0.651 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.328 Inches Nominal
Material Accommodated Thickness:	0.180 Inches Minimum And 0.239 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.069 Inches Minimum And 0.076 Inches Maximum
Material:	Steel Ejector Spring
Material:	Steel Eyelet
Material:	Steel Pin
Material:	Steel Stud
Surface Treatment:	Cadmium Overall And Chromate Overall

# **How to Order**

Order this turnlock fastener stud from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1127000-7">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1127000-7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.